## NSN 5930-00-081-4814

Thermostatic Switch - Page 1 of 2

**Thread Class:** 

2b all threaded hole

Contact Voltage Rating In Volts: 240.0 ac at sea level second voltage



View Online at https://aerobasegroup.com/nsn/5930-00-081-4814

Overall Length:
3.469 inches
Overall Height:
4.813 inches
Overall Width:
2.000 inches
Body Length:
3.469 inches
Distance Between Mounting Facility Centers:
1.000 inches
Capillary Tube Length:
76.0 inches
Tempurature Sensing Element Type:
Capillary tube
Mounting Method:
Threaded hole
Features Provided:
Electrical access port and automatic reset
Contact Action Stimulus:
Increase
Thread Size:
0.190 inches all threaded hole
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Screw
Contact Load Current Rating:
20.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point adjustable, preset and deactuation point adjustable, preset
Contact Adjustment Range:
-35.00 to 0.00 actuation point degrees fahrenheit and -35.00 to 0.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External actuation point knob and external deactuation point knob
Contact Stimulus Rating:
0.00 actuation point degrees fahrenheit and -4.00 deactuation point degrees fahrenheit

## **NSN 5930-00-081-4814** Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Thread Series Designator:
Unef all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0