NSN 5930-00-082-1655

Pressure Switch - Page 1 of 2

0.438 inches single connection

Thread Class:
2b all threaded hole
Inside Diameter:

Overall Length: 2.500 inches Overall Height: 3.312 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5930-00-082-1655

2.594 inches
Longest Horizontal Distance Between Mounting Centers:
1.500 inches
Longest Vertical Distance Between Mounting Centers:
1.500 inches
Pressure Switch Type:
Absolute
Mounting Method:
Base and threaded hole
Features Provided:
Electrical box connector
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.438 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
3.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable, preset and actuation point adjustable, preset
Contact Adjustment Range:
+24.00 to 100.00 actuation point inches of mercury and +24.00/+100.00 deactuation point inches of mercury
Contact Adjustment Type:
External deactuation point screw and external actuation point screw
Contact Stimulus Rating:
32.00 actuation point inches of mercury and 2.00 differential point inches of mercury and 5.00 differential point inches of mercury

NSN 5930-00-082-1655

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

115.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0