

View Online at <https://aerobasegroup.com/nsn/5930-00-085-0353>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Bushing Length:**

1.358 inches

**Body Length:**

0.350 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.153 inches

**Actuator Height:**

0.144 inches

**Actuator Free Position Height:**

Between 0.004 inches and 0.020 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.438 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

5.0 ounces

**Switch Actuating Force:**

30.0 ounces

**Actuator Movement:**

Between 0.010 pretravel inches and 0.125 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0