NSN 5930-00-085-0602

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-085-0602

Internal deactuation point hex nut and internal actuation point hex nut

Overall Langth
Overall Length: 6.230 inches
Overall Height:
2.710 inches
Overall Width:
4.750 inches
Unthreaded Mounting Hole Diameter:
0.265 inches
Longest Horizontal Distance Between Mounting Centers:
4.250 inches
Longest Vertical Distance Between Mounting Centers:
3.100 inches
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -30.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
4500.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Four position rectangular
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
4.0 amperes resistive load second voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+20.00/+100.00 actuation point pounds per square inch and +20.00 to 100.00 deactuation point pounds per square inch
Contact Adjustment Type:

NSN 5930-00-085-0602

Pressure Switch - Page 2 of 2



Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0