# NSN 5930-00-085-4662

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-085-4662

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.250 inches single mounting facility

# **Overall Length:**

1.957 inches

### **Overall Height:**

1.031 inches

#### **Overall Width:**

1.125 inches

#### Shaft Diameter:

0.125 inches single actuator

## Shaft Length:

1.000 inches single actuator

#### **Nonturn Device Radius:**

# 0.375 inches at 3: 00 o'clock

### Individual Section Quantity:

1

Nonturn Device Type:

Tab at 3: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

# Pole Quantity:

2 single section rear

### **Throw Quantity:**

5 single section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Thread Size:**

0.250 inches single mounting facility

### Contact Voltage Rating In Volts:

6.0 dc at sea level

# Switch Actuator Indexing Position Quantity:

6 single actuator

# Shaft Type:

Round single actuator

# Terminal Type:

Clip

# **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-085-4662

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 3.5 amperes resistive load dc at sea level **Precious Material And Location:** Clips and rotor contact surfaces silver **Precious Material:** Silver Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0