

View Online at <https://aerobasegroup.com/nsn/5930-00-085-8093>

Overall Height:

1.859 inches

Overall Width:

1.734 inches

Body Thickness:

0.063 inches

Unthreaded Mounting Hole Diameter:

0.126 inches single mounting facility

Distance Between Mounting Facility Centers:

1.362 inches single mounting facility

Longest Horizontal Distance Between Mounting Centers:

1.562 inches single mounting facility

Operating Temperature Range:

-55.0 to 85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

5 single section front

Mounting Method:

Strut single mounting facility and unthreaded hole single mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks single section rear

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Switch section, rotary

Test Data Document:

81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0