NSN 5930-00-085-8093

Rotary Switch Section - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-085-8093

Overall Height:
1.859 inches
Overall Width:
1.734 inches
Body Thickness:
0.063 inches
Unthreaded Mounting Hole Diameter:
0.126 inches single mounting facility
Distance Between Mounting Facility Centers:
1.362 inches single mounting facility
Longest Horizontal Distance Between Mounting Centers:
1.562 inches single mounting facility
Operating Tempurature Range:
-55.0 to 85.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear
Throw Quantity:
5 single section front
Mounting Method:
Strut single mounting facility and unthreaded hole single mounting facility
Contact Voltage Rating In Volts:
300.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Two position in-line single mounting facility
Terminal Type:
Tab, solder lug
Contact Switching Action:
Makes before breaks single section rear
Contact Load Current Rating:
500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level
Style Designator:
Switch section, rotary
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

NSN 5930-00-085-8093

Rotary Switch Section - Page 2 of 2



Fiig:

A052b0