

View Online at <https://aerobasegroup.com/nsn/5930-00-086-0723>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

0.845 inches

**Body Width:**

0.250 inches

**Body Height:**

0.437 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.094 inches

**Actuator Length:**

0.120 inches

**Actuator Style:**

Rectangular

**Actuator Width:**

0.120 inches

**Actuator Free Position Height:**

0.093 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

2.0 ounces

**Switch Actuating Force:**

Between 3.0 ounces and 8.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 7.500 amperes inductive dc and 4.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0