

View Online at <https://aerobasegroup.com/nsn/5930-00-086-0724>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Body Length:

0.845 inches

Body Width:

0.250 inches

Body Height:

0.761 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

Between 0.087 inches and 0.090 inches

Actuator Style:

Round

Actuator Diameter:

0.120 inches

Actuator Free Position Height:

0.100 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 8.0 ounces and 16.0 ounces

Actuator Movement:

Between 0.060 pretravel inches and 0.012 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 9.000 amperes inductive dc and 3.000 amperes lamp dc and 9.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0