

View Online at <https://aerobasegroup.com/nsn/5930-00-086-0724>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Body Length:**

0.845 inches

**Body Width:**

0.250 inches

**Body Height:**

0.761 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

Between 0.087 inches and 0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.120 inches

**Actuator Free Position Height:**

0.100 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

2 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 8.0 ounces and 16.0 ounces

**Actuator Movement:**

Between 0.060 pretravel inches and 0.012 overtravel inches and 0.025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 9.000 amperes inductive dc and 3.000 amperes lamp dc and 9.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Precious Material And Location:**

Contacts gold

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0