## NSN 5930-00-086-2478

Rotary Switch - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5930-00-086-2478

2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 7.311 inches **Overall Height:** 1.875 inches **Overall Width:** 1.609 inches First Flat Length: 0.500 inches single actuator Flat Height: 0.218 inches single actuator **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.250 inches single actuator **Nonturn Device Radius:** 0.531 inches at 9: 00 o'clock **Individual Section Quantity:** 9 **Nonturn Device Type:** Tab at 9: 00 o'clock **Switch Contact Basic Design:** Nonpile-up nonsymmetrical **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 5 single actuator **Shaft Type:** Round, flatted single actuator

Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type:

Fixed stop single actuator

**Terminal Type:** Tab, solder lug

## NSN 5930-00-086-2478

Rotary Switch - Page 2 of 2



## **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts and rotor blades silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0