

View Online at <https://aerobasegroup.com/nsn/5930-00-086-7649>

Thread Class:

2a single mounting facility

Thread Length:

0.365 inches single mounting facility and 0.375 inches single mounting facility

Overall Length:

Between 2.360 inches and 2.480 inches

Overall Height:

Between 1.280 inches and 1.340 inches

Overall Width:

Between 1.220 inches and 1.280 inches

First Flat Length:

0.280 inches single actuator and 0.340 inches single actuator

Flat Height:

0.178 inches single actuator and 0.198 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.250 inches single actuator

Shaft Length:

0.720 inches single actuator and 0.780 inches single actuator

Nonturn Device Radius:

0.521 inches at 3:00 o'clock and 0.541 inches at 3:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical and nonpile-up nonsymmetrical

Pole Quantity:

1 1st section rear

Throw Quantity:

1 1st section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

45.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 2nd section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0