

View Online at <https://aerobasegroup.com/nsn/5930-00-086-9859>

Thread Class:

2a single mounting facility

Thread Length:

0.359 inches single mounting facility and 0.391 inches single mounting facility

Overall Length:

3.125 inches

Overall Height:

Between 1.109 inches and 1.141 inches

Overall Width:

Between 1.296 inches and 1.328 inches

First Flat Length:

0.375 inches 2nd actuator

Flat Height:

0.156 inches 2nd actuator

Shaft Diameter:

0.265 inches 1st actuator

Shaft Length:

1.250 inches 2nd actuator

Nonturn Device Radius:

0.531 inches at 9:00 o'clock

Individual Section Quantity:

2

Nonturn Device Type:

Tab at 9:00 o'clock

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 all actuators

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees all actuators

Switch Actuator Stop Device Type:

Fixed stop all actuators

Contact Load Current Rating:

750.0 milliamperes resistive load ac at sea level

Style Designator:

Square wafer, panel mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0