

View Online at <https://aerobasegroup.com/nsn/5930-00-087-1118>

Thread Class:

2a single mounting facility

Thread Length:

0.190 inches single mounting facility

Overall Length:

0.965 inches

Overall Height:

0.800 inches

Overall Width:

0.390 inches

Shaft Diameter:

0.160 inches single actuator

Shaft Length:

0.065 inches single actuator

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Cam actuated

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary single switch single section rear

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0