# NSN 5930-00-087-1118

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-087-1118

# **Thread Class:**

2a single mounting facility

# Thread Length:

0.190 inches single mounting facility

# **Overall Length:**

0.965 inches

# **Overall Height:**

0.800 inches

#### **Overall Width:**

0.390 inches

# Shaft Diameter:

0.160 inches single actuator

# Shaft Length:

0.065 inches single actuator

# Individual Section Quantity:

1

# Switch Contact Basic Design:

Nonpile-up nonsymmetrical

# **Mounting Method:**

Threaded bushing single mounting facility

# **Features Provided:**

Cam actuated

# Thready Qty Per Inch (tpi):

40 single mounting facility

# Thread Size:

0.250 inches single mounting facility

# **Contact Voltage Rating In Volts:**

30.0 dc at sea level

# Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary single switch single section rear

# Switch Actuator Indexing Position Quantity:

2 single actuator

#### Shaft Type:

Round, slotted single actuator

# **Terminal Type:**

Tab, solder lug

# **Contact Switching Action:**

Breaks before makes single section rear

# Switch Actuator Positioning Increment:

90.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# NSN 5930-00-087-1118

Rotary Switch - Page 2 of 2



# **Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

#### Style Designator:

In-line, cam actuated

# **Thread Series Designator:**

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A052b0