

View Online at <https://aerobasegroup.com/nsn/5930-00-087-1808>

Thread Class:

2a single mounting facility

Thread Length:

0.280 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

1.390 inches

Overall Height:

1.060 inches

Overall Width:

1.060 inches

First Flat Length:

0.322 inches single actuator

Flat Height:

0.154 inches single actuator and 0.158 inches single actuator

Shaft Diameter:

0.247 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.640 inches single actuator

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 12: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

1 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

28 single mounting facility

Thread Size:

0.438 inches single mounting facility

Contact Voltage Rating In Volts:

14.0 dc at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Quick disconnect, male

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

20.0 amperes resistive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Un single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0