

View Online at <https://aerobasegroup.com/nsn/5930-00-087-1808>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.280 inches single mounting facility

**Hazardous Locations/environmental Protection:**

Moisture resistant

**Overall Length:**

1.390 inches

**Overall Height:**

1.060 inches

**Overall Width:**

1.060 inches

**First Flat Length:**

0.322 inches single actuator

**Flat Height:**

0.154 inches single actuator and 0.158 inches single actuator

**Shaft Diameter:**

0.247 inches single actuator and 0.251 inches single actuator

**Shaft Length:**

0.640 inches single actuator

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 12: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

1 single section rear

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Metallic inclosure

**Thready Qty Per Inch (tpi):**

28 single mounting facility

**Thread Size:**

0.438 inches single mounting facility

**Contact Voltage Rating In Volts:**

14.0 dc at sea level

**Shaft Flat/slot Angular Location:**

0.0 degrees from nonturn device single actuator

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Quick disconnect, male

**Contact Switching Action:**

Breaks before makes single section rear

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

20.0 amperes resistive load dc at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Un single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0