

View Online at <https://aerobasegroup.com/nsn/5930-00-088-4675>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

Between 0.875 inches and 1.000 inches

Overall Height:

1.875 inches

Overall Width:

0.500 inches

Bushing Length:

0.500 inches

Body Length:

Between 0.875 inches and 1.000 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Actuator Style:

Round

Actuator Height:

0.875 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive ac

Special Features:

On and off indicator plate

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 wire lead

Specification Data:

96906-ms16656 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0