

View Online at <https://aerobasegroup.com/nsn/5930-00-088-4675>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

Between 0.875 inches and 1.000 inches

**Overall Height:**

1.875 inches

**Overall Width:**

0.500 inches

**Bushing Length:**

0.500 inches

**Body Length:**

Between 0.875 inches and 1.000 inches

**Body Width:**

0.500 inches

**Body Height:**

0.500 inches

**Actuator Style:**

Round

**Actuator Height:**

0.875 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive ac

**Special Features:**

On and off indicator plate

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 wire lead

**Specification Data:**

96906-ms16656 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0