

View Online at <https://aerobasegroup.com/nsn/5930-00-088-5522>

Thread Class:

2a single mounting facility

Thread Length:

0.440 inches single mounting facility

Overall Length:

3.640 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.214 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.750 inches single actuator

Overall Diameter:

1.190 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section front

Throw Quantity:

5 single section rear

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Spring return

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Momentary Position:

Clockwise single actuator and counterclockwise single actuator

Rotor Through Connection Quantity:

2 single section

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks, breaks before makes single section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level and 500.0 milliamperes inductive load dc at sea level

Special Features:

2pdt momentary switch on rear of rotary switch actuated by pushing shaft

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0