NSN 5930-00-088-5542

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-088-5542

Thread Class:

2a single mounting facility

Thread Length:

0.430 inches single mounting facility

Overall Length:

2.190 inches

First Flat Length:

0.380 inches single actuator

Flat Height:

0.214 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

1.110 inches single actuator

Overall Diameter:

Between 1.100 inches and 1.190 inches

Individual Section Quantity:

1

Operating Tempurature Range:

-65.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

NSN 5930-00-088-5542

Rotary Switch - Page 2 of 2



Sty	ما	D	20	in	n	2	ŧ۸	r	
JLY	ı	יש	င၁	ıу	••	а	ιυ	ш	

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0