

View Online at <https://aerobasegroup.com/nsn/5930-00-089-2203>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

3.040 inches

**Body Width:**

1.000 inches

**Body Height:**

1.750 inches

**Unthreaded Mounting Hole Diameter:**

0.172 inches

**Actuator Style:**

Roller plunger

**Actuator Free Position Height:**

1.953 inches

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.180 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

13.0 ounces

**Actuator Movement:**

Between 0.015 pretravel inches and 0.140 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0