NSN 5930-00-090-4302

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-090-4302

Contact Load Current Rating At Maximum Rated Voltage:

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.050 inches
Overall Height:
1.200 inches
Overall Width:
0.692 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
1.110 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.600 inches
Maximum Voltage Rating In Volts:
125.0 ac and 28.0 dc
Inclosure Type:
Hermetically sealed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
5.0 ounces
Switch Actuating Force:
Between 11.0 ounces and 23.0 ounces
Actuator Movement:
Between 0.060 pretravel inches and 0.015 overtravel inches and 10.0 differential degrees

25.000 amperes resistive dc and 10.000 amperes inductive dc and 3.500 amperes lamp dc and 5.000 amperes motor dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

NSN 5930-00-090-4302

Sensitive Switch - Page 2 of 2



Terminal	Type A	And C	luantity:
_			

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0