NSN 5930-00-090-4302

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-090-4302

Contact Load Current Rating At Maximum Rated Voltage:

| Body Style: |
|--|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Weatherproof |
| Overall Length: |
| 1.940 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.050 inches |
| Overall Height: |
| 1.200 inches |
| Overall Width: |
| 0.692 inches |
| Body Length: |
| 1.940 inches |
| Body Width: |
| 0.687 inches |
| Case Material: |
| Plastic |
| Unthreaded Mounting Hole Diameter: |
| 0.139 inches |
| Actuator Length: |
| 1.110 inches |
| Actuator Style: |
| Leaf |
| Actuator Free Position Height: |
| 0.600 inches |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 28.0 dc |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 5.0 ounces |
| Switch Actuating Force: |
| Between 11.0 ounces and 23.0 ounces |
| Actuator Movement: |
| Between 0.060 pretravel inches and 0.015 overtravel inches and 10.0 differential degrees |

25.000 amperes resistive dc and 10.000 amperes inductive dc and 3.500 amperes lamp dc and 5.000 amperes motor dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

NSN 5930-00-090-4302

Sensitive Switch - Page 2 of 2



| Terminal | Type / | And (| Quanti | ty: |
|----------|--------|-------|--------|-----|
| _ | | | | |

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0