

View Online at <https://aerobasegroup.com/nsn/5930-00-090-9368>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

5.750 inches

**Overall Height:**

2.688 inches

**Overall Width:**

5.000 inches

**Body Height:**

2.750 inches

**Unthreaded Mounting Hole Diameter:**

0.281 inches

**Longest Horizontal Distance Between Mounting Centers:**

2.406 inches

**Shortest Horizontal Distance Between Mounting Centers:**

0.656 inches

**Longest Vertical Distance Between Mounting Centers:**

3.281 inches

**End Application:**

Forrestal class cv, ohio class ssn ship (trident), nimitz class cvn, powhatan class t-atf 166, waters class tags-45, kilauea class t-ae 26, austin ship class lpd-4 amphibious transport docks.

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

900.00 pounds per square inch gage

**Mounting Facility Pattern:**

Isosceles triangle

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Criticality Code Justification:**

Feat

**Terminal Type:**

Screw

**Contact Load Current Rating:**

8.6 amperes resistive load fourth voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+60.00/+900.00 actuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point screw

**Contact Voltage Rating In Volts:**

440.0 dc at sea level third voltage

**Special Features:**

Weapon system essential

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Rectangular

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0