

View Online at <https://aerobasegroup.com/nsn/5930-00-090-9368>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.750 inches

Overall Height:

2.688 inches

Overall Width:

5.000 inches

Body Height:

2.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Longest Horizontal Distance Between Mounting Centers:

2.406 inches

Shortest Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

End Application:

Forrestal class cv, ohio class ssn ship (trident), nimitz class cvn, powhatan class t-atf 166, waters class tags-45, kilauea class t-ae 26, austin ship class lpd-4 amphibious transport docks.

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Proof Pressure:

900.00 pounds per square inch gage

Mounting Facility Pattern:

Isosceles triangle

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Criticality Code Justification:

Feat

Terminal Type:

Screw

Contact Load Current Rating:

8.6 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+60.00/+900.00 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

440.0 dc at sea level third voltage

Special Features:

Weapon system essential

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0