NSN 5930-00-090-9416

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-090-9416

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

4.000 inches

Overall Height:

4.296 inches

Overall Width:

1.300 inches

Case Material:

Plastic

Actuator Length:

1.570 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

2.310 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.312 inches

Housing Length:

4.000 inches

Housing Width:

1.300 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.625 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.250 inches

Maximum Voltage Rating In Volts:

480.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

32.0 ounces

NSN 5930-00-090-9416

Sensitive Switch - Page 2 of 2



Actuator Movement:

Between 0.219 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 20.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0