NSN 5930-00-090-9417

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-090-9417

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof and vaportight
Overall Length:
4.000 inches
Overall Height:
4.377 inches
Overall Width:
1.300 inches
Case Material:
Plastic
Actuator Length:
1.562 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
3.297 inches
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.312 inches
Housing Height:
3.250 inches
Housing Length:
2.160 inches
Housing Width:
1.300 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.625 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
8.0 ounces
Switch Actuating Force:

32.0 ounces

NSN 5930-00-090-9417

Sensitive Switch - Page 2 of 2



Δ	ctu	ator	·Mc	WA	mar	١+.
н	CLU	alui	IVIC	vei	пег	H.

Between 0.219 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

150.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0