## NSN 5930-00-091-1428



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-091-1428 **Body Style:** Hole mounted **Overall Length:** 2.094 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.875 inches **Overall Height:** 1.125 inches **Overall Width:** 0.675 inches **Body Length:** 1.094 inches **Body Width:** 0.406 inches **Body Height:** 0.625 inches **Case Material:** Plastic **Unthreaded Mounting Hole Diameter:** 0.126 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.375 inches **Actuator Style:** Round **Actuator Diameter:** 0.125 inches **Actuator Height:** 0.031 inches **Actuator Free Position Height:** 0.094 inches **Maximum Voltage Rating In Volts:** 250.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Unthreaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit

**Switch Release Force:** 2.0 grams

**Switch Actuating Force:** 

33.0 grams

## NSN 5930-00-091-1428

Sensitive Switch - Page 2 of 2



## **Actuator Movement:**

Between 0.100 pretravel inches and 0.080 overtravel inches and 0.030 differential inches

## **Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0