

View Online at <https://aerobasegroup.com/nsn/5930-00-091-8851>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.375 inches

**Body Length:**

0.876 inches

**Body Width:**

0.346 inches

**Body Height:**

0.600 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.030 inches

**Actuator Height:**

0.150 inches

**Actuator Free Position Height:**

0.475 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

19.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.003 overtravel inches and 0.004 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:**

One mtg hole elongated to 0.098 in.

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0