

View Online at <https://aerobasegroup.com/nsn/5930-00-093-7923>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Weatherproof

**Overall Length:**

2.875 inches

**Overall Height:**

0.990 inches

**Overall Width:**

0.990 inches

**Body Diameter:**

0.990 inches

**Bushing Length:**

0.440 inches

**Body Length:**

1.120 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

0.680 inches

**Actuator Height:**

0.700 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

6 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

2.000 amperes resistive dc and 1.000 amperes inductive dc and 750.000 milliamperes lamp dc and 2.000 amperes resistive ac and 1.000 amperes inductive ac and 750.000 milliamperes lamp ac

**Special Features:**

Two terminals for lamps

**Precious Material And Location:**

Contact surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

20 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0