

View Online at <https://aerobasegroup.com/nsn/5930-00-093-7993>

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.355 inches and 0.365 inches

**Body Length:**

0.500 inches

**Body Width:**

0.450 inches

**Body Height:**

Between 0.342 inches and 0.358 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.214 inches

**Actuator Height:**

0.580 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0