

View Online at <https://aerobasegroup.com/nsn/5930-00-094-6231>

**Body Style:**

Bushing mount

**Bushing Length:**

Between 0.427 inches and 0.447 inches

**Body Length:**

Between 0.495 inches and 0.505 inches

**Body Width:**

Between 0.440 inches and 0.460 inches

**Body Height:**

Between 0.400 inches and 0.420 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

Between 0.438 inches and 0.458 inches

**Actuator Width:**

Between 0.195 inches and 0.205 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 24.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0