

View Online at <https://aerobasegroup.com/nsn/5930-00-094-6232>

Body Style:

Bushing mount

Bushing Length:

Between 0.427 inches and 0.447 inches

Body Length:

Between 0.495 inches and 0.505 inches

Body Width:

Between 0.440 inches and 0.460 inches

Body Height:

Between 0.400 inches and 0.420 inches

Actuator Style:

Rectangular

Actuator Height:

Between 0.438 inches and 0.458 inches

Actuator Width:

Between 0.195 inches and 0.205 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 24.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0