NSN 5930-00-096-3333



Rotary Switch - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/5930-00-096-3333	
Thread Class:	
2a single mounting facility	
Thread Length:	
0.375 inches single mounting facility	
Overall Length:	
2.062 inches	
Overall Height:	
1.594 inches	
Overall Width:	
1.422 inches	
Shaft Diameter:	
0.247 inches single actuator and 0.251 inches single actuator	
Shaft Length:	
0.875 inches single actuator	
Nonturn Device Radius:	
0.531 inches at 3: 00 o'clock	
Individual Section Quantity:	
1	
Nonturn Device Type:	
Tab at 3: 00 o'clock	
Operating Tempurature Range:	
-25.0/+85.0 degrees celsius	
Switch Contact Basic Design:	
Nonpile-up symmetrical	
Pole Quantity:	
2 single section rear	
Throw Quantity:	
4 single section rear	
Mounting Method:	
Threaded bushing single mounting facility	
Thread Size:	
0.375 inches single mounting facility	

Contact Voltage Rating In Volts:

30.0 dc at sea level

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

NSN 5930-00-096-3333

Rotary Switch - Page 2 of 2



30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

300.0 milliamperes resistive load dc at sea level and 30.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0