

View Online at <https://aerobasegroup.com/nsn/5930-00-098-8913>

Thread Class:

2a

Hazardous Locations/environmental Protection:

Weatherproof

Body Diameter:

Between 0.985 inches and 1.015 inches

Bushing Length:

Between 0.970 inches and 1.030 inches

Body Length:

0.980 inches

Actuator Style:

Round

Actuator Diameter:

0.250 inches

Actuator Height:

0.375 inches

Actuator Free Position Height:

1.030 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

64.0 ounces

Switch Actuating Force:

192.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 4.000 amperes inductive dc and 2.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

1 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0