

View Online at <https://aerobasegroup.com/nsn/5930-00-098-8913>

**Thread Class:**

2a

**Hazardous Locations/environmental Protection:**

Weatherproof

**Body Diameter:**

Between 0.985 inches and 1.015 inches

**Bushing Length:**

Between 0.970 inches and 1.030 inches

**Body Length:**

0.980 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.375 inches

**Actuator Free Position Height:**

1.030 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

64.0 ounces

**Switch Actuating Force:**

192.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.020 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 4.000 amperes inductive dc and 2.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

1 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0