

View Online at <https://aerobasegroup.com/nsn/5930-00-098-8923>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Body Diameter:**

0.531 inches

**Bushing Length:**

1.190 inches

**Body Length:**

0.650 inches

**Actuator Diameter:**

1.250 inches

**Actuator Height:**

1.050 inches

**Actuator Color:**

Red single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 8.000 amperes inductive dc and 4.000 amperes lamp dc and 10.000 amperes motor dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0