## NSN 5930-00-098-8923

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-098-8923 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Watertight **Body Diameter:** 0.531 inches **Bushing Length:** 1.190 inches **Body Length:** 0.650 inches **Actuator Diameter:** 1.250 inches **Actuator Height:** 1.050 inches **Actuator Color:** Red single actuator **Maximum Voltage Rating In Volts:** 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded bushing **Features Provided:** Actuator seal Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 1 two circuit, double break/double make, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 10.000 amperes resistive dc and 8.000 amperes inductive dc and 4.000 amperes lamp dc and 10.000 amperes motor dc **Thread Series Designator:** Unef **Terminal Type And Quantity:** 4 tab, solder lug Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5930-00-098-8923

Push Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0