

View Online at <https://aerobasegroup.com/nsn/5930-00-098-9080>

Thread Class:

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

Overall Length:

3.501 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.211 inches and 0.221 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.938 inches single actuator

Overall Diameter:

1.375 inches

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 3: 00 o'clock

Operating Temperature Range:

-65.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 each section rear

Throw Quantity:

5 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

330.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

350.0 milliamperes resistive load and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Circular wafer, bushing mount

Test Data Document:

81349-mil-s-3786/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0