## NSN 5930-00-098-9100

Lever Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-098-9100 **Thread Class:** 2b **Body Style:** Hole mounted **Body Length:** 1.313 inches **Body Width:** 0.438 inches **Body Height:** 1.875 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.625 inches **Actuator Style:** Rectangular **Actuator Height:** 0.625 inches **Actuator Width:** 0.187 inches **Actuator Position-action Relationship:** Down position momentary and center position maintained **Maximum Voltage Rating In Volts:** 115.0 ac and 12.0 dc **Inclosure Type:** Uninclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Nonpile-up Contact Arrangement:** 4 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 3.000 amperes resistive dc and 230.000 milliamperes resistive ac **Special Features:** Spring return from position to position 2 **Precious Material And Location:** Contact surfaces silver **Thread Series Designator:** Unc

**Terminal Type And Quantity:** 12 tab, solder lug

## NSN 5930-00-098-9100

Lever Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0