

View Online at <https://aerobasegroup.com/nsn/5930-00-098-9669>

Thread Class:

2a

Body Style:

Bushing/hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.850 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

Overall Height:

1.688 inches

Overall Width:

0.375 inches

Bushing Length:

0.563 inches

Body Length:

0.850 inches

Body Width:

0.375 inches

Body Height:

0.688 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.094 inches

Actuator Style:

Round

Actuator Diameter:

0.125 inches

Actuator Height:

0.320 inches

Actuator Free Position Height:

1.000 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thread Size:

0.375 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

8.0 ounces

Switch Actuating Force:

36.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.187 overtravel inches and 0.030 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0