

View Online at <https://aerobasegroup.com/nsn/5930-00-098-9669>

**Thread Class:**

2a

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

0.850 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.500 inches

**Overall Height:**

1.688 inches

**Overall Width:**

0.375 inches

**Bushing Length:**

0.563 inches

**Body Length:**

0.850 inches

**Body Width:**

0.375 inches

**Body Height:**

0.688 inches

**Case Material:**

Metal

**Unthreaded Mounting Hole Diameter:**

0.094 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.125 inches

**Actuator Height:**

0.320 inches

**Actuator Free Position Height:**

1.000 inches

**Maximum Voltage Rating In Volts:**

30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thread Size:**

0.375 inches

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Release Force:**

8.0 ounces

**Switch Actuating Force:**

36.0 ounces

**Actuator Movement:**

Between 0.070 pretravel inches and 0.187 overtravel inches and 0.030 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0