

View Online at <https://aerobasegroup.com/nsn/5930-00-099-0121>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.352 inches

**Body Length:**

Between 0.833 inches and 0.853 inches

**Body Width:**

Between 0.495 inches and 0.505 inches

**Body Height:**

Between 0.465 inches and 0.475 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.114 inches and 0.116 inches

**Actuator Height:**

Between 0.390 inches and 0.410 inches

**Actuator Position-action Relationship:**

Up position momentary and down position momentary and center position maintained

**Maximum Voltage Rating In Volts:**

125.0 ac and 24.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0