

View Online at <https://aerobasegroup.com/nsn/5930-00-099-0552>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Unthreaded Mounting Hole Diameter:

0.114 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Length:

0.110 inches

Actuator Style:

Rectangular

Actuator Height:

0.063 inches

Actuator Width:

0.165 inches

Actuator Free Position Height:

0.650 inches

Actuator Adapter Style:

Leaf

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

End Application:

Wasp class lhd, command control and communications sys 427m, tarawa class lha, boat davits, emory s. Land class as, usns henry j. Kaiser class tao, forrestral class cv

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

6.0 ounces

Criticality Code Justification:

Feat

Switch Actuating Force:

15.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.050 overtravel inches and 0.025 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Weapon system essential

Terminal Type And Quantity:

3 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0