

View Online at <https://aerobasegroup.com/nsn/5930-00-099-0552>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

1.094 inches

**Body Width:**

0.400 inches

**Body Height:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Length:**

0.110 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.063 inches

**Actuator Width:**

0.165 inches

**Actuator Free Position Height:**

0.650 inches

**Actuator Adapter Style:**

Leaf

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**End Application:**

Wasp class lhd, command control and communications sys 427m, tarawa class lha, boat davits, emory s. Land class as, usns henry j. Kaiser class tao, forrestrai class cv

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

6.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

15.0 ounces

**Actuator Movement:**

Between 0.050 pretravel inches and 0.050 overtravel inches and 0.025 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0