NSN 5930-00-099-2103



Sensitive Switch - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5930-00-099-2103 **Body Style: Bushing mounted Overall Length:** 2.240 inches **Actuator Length:** 2.000 inches **Actuator Style:** Adjustable arm **Actuator Diameter:** 0.180 inches **Actuator Height:** 1.240 inches **Actuator Width:** 2.500 inches **Housing Diameter:** 1.000 inches **Housing Length:** 1.000 inches **Housing Bushing Length:** 0.340 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Hermetically sealed Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.469 inches **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Switch Release Force:** 20.0 ounces **Switch Actuating Force:**

48.0 inch-ounces

Actuator Movement:

4.0 pretravel degrees and 35.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes inductive dc and 4.000 amperes motor dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 wire lead

NSN 5930-00-099-2103

Sensitive Switch - Page 2 of 2



-					
•	he	1+	18	Δ	•

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0