

View Online at <https://aerobasegroup.com/nsn/5930-00-100-6581>

Thread Class:

2b single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

5.813 inches

Overall Height:

2.719 inches

Overall Width:

2.406 inches

First Flat Length:

1.438 inches single actuator

Shaft Length:

1.875 inches single actuator

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

6

Knob Specificationial Markings:

Arrow sign

Longest Horizontal Distance Between Mounting Centers:

1.640 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

1.640 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

3 each section rear

Mounting Method:

Bracket single mounting facility and threaded hole single mounting facility

Features Provided:

Actuator knob

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0