

View Online at <https://aerobasegroup.com/nsn/5930-00-100-7171>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Actuator Style:

Roller arm

Actuator Free Position Height:

2.086 inches

Actuator Roller Diameter:

0.375 inches

Actuator Roller Width:

0.125 inches

Housing Length:

1.625 inches

Housing Width:

1.109 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

1.335 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

1.094 inches

Maximum Voltage Rating In Volts:

30.0 dc

Inclosure Type:

Hermetically sealed

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

96.0 ounces

Actuator Movement:

Between 0.085 pretravel inches and 0.187 overtravel inches and 0.040 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0