NSN 5930-00-101-9656

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-101-9656 **Thread Class:** 2b **Body Style:** Hole mounted **Overall Length:** 6.031 inches **Overall Height:** 2.062 inches **Overall Width:** 2.953 inches **Actuator Style:** Roller plunger **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.125 inches **Housing Height:** 2.031 inches **Housing Length:** 6.031 inches **Housing Width:** 2.156 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 4.125 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.500 inches **Maximum Voltage Rating In Volts:** 600.0 ac and 600.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.250 inches **Nonpile-up Contact Arrangement:** 1 two circuit, one position momentary single switch unit

Switch Actuating Force:

40.0 ounces

Actuator Movement:

0.080 pretravel inches and 0.170 overtravel inches and 0.030 differential inches

NSN 5930-00-101-9656

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 10.000 amperes resistive ac and 1.200 amperes inductive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0